

BUKHARA REGIONAL COLLECTOR – FUNDAMENTAL OF OPTIONAL OPTIONS FOR USE OF EXCAVATORS FOR CLEANING DRINKS

Makhmudova Maftuna Maqsud qizi

“TIAME” NRU Bukhara Institute of Natural Resources Management

mmm926458@gmail.com

Sobirov Komil Sodiq ugli

“TIAME” NRU Bukhara Institute of Natural Resources Management

Ergashev Saidolim Inomjon ugli

“TIAME” NRU Bukhara Institute of Natural Resources Management

ANNOTATION

The article contains excavators in Bukhara region and their optimal options for the selection of excavators, taking into account their hydraulic parameters and the importance of collector-ditches, as well as the timely completion of work on its cleaning and reconstruction. Substantiation using formulas. It also provides advice on the effective use of existing excavators.

Keywords: Collector, ditch, excavator, reconstruction, bucket, productivity, soil, labor.

Annotatsiya

Maqolada viloyatda mavjud ochiq kollektor - zovurlar ularning gidravlik parametrlarini inobatga olgan holda ekskavatorlarni tanlash va kollektor- zovurlarning ahamiyati hamda uni tozalash va rekonstruksiya qilishda ishlarini o'z muddatlarida bajarishni ta'minlash masadida Buxoro viloyati kollektor – zovurlarni tozalashda talab etiladigan ekskavatorlar va ularning maqbul variantlarini mavjud formulalardan foydalanib asoslash. Shuningdek mavjud ekskavatorlardan samarali foydalanish bo'yicha tavsiyalar berish yoritilgan.

Kalit so'zlari: Kollektor, zovur, ekskavator, rekonstruksiya, cho'mich, ish unumdorlik, grunt, mehnat sarfi.

INTRODUCTION

Currently in the whole Bukhara region 295783.85 hectares irrigated area is available, with a strongly saline area of 4.5%, an average saline area of 26%, and a weakly saline area of 56% per hectare. In order to reduce salinity and groundwater levels in these areas, the total area across the region 2844.48 km² There are collector drains. Including inter-farm collectors 2097.45 km², the internal collectors of the farm is 4728.9 km².

According to a number of researchers, the repair and reconstruction of collector-ditches accounts for 25-30% of the total length each year. Observations show that in the territory of Bukhara region, cleaning and reconstruction of collector-ditches with different hydraulic parameters are carried out with excavators of different models. To date, no scientifically based recommendations for the use of excavators based on the hydraulic parameters of the collector-

pipes have been developed and the required number of them has not been determined. This requires substantiation of the optimal number of excavators in accordance with the hydraulic parameters of the excavator models and specifications, as well as the volume of work. This increases the productivity of the work performed and reduces the cost of the work performed. In order to keep the reclamation condition of lands at the required level, it is necessary to predict the demand for the composition and number of machines (to know the annual demand) in order to ensure that the required content, number and types of machines are constantly working. Therefore, in this article we will consider a method of theoretical determination of the need for modern excavators only in the composition of reclamation machines for the repair and reconstruction of collector-ditches in Bukhara region. The main indicator of excavators is productivity. Calculation of excavator productivity using expressions and norms. there is a need to predict the demand for the composition and number of machines (to know the annual demand accurately). Therefore, in this article we will consider a method of theoretical determination of the need for modern excavators only in the composition of reclamation machines for the repair and reconstruction of collector-ditches in Bukhara region. The main indicator of excavators is productivity. Calculation of excavator productivity using expressions and norms. there is a need to predict the demand for the composition and number of machines (to know the annual demand accurately). Therefore, in this article we will consider a method of theoretical determination of the need for modern excavators only in the composition of reclamation machines for the repair and reconstruction of collector-ditches in Bukhara region. The main indicator of excavators is productivity. Calculation of excavator productivity using expressions and norms. work productivity. Calculation of excavator performance using expressions and norms. work productivity. Calculation of excavator productivity using expressions and norms.

Using the existing theoretical formulas, we substantiate the number of excavators required during the season in the Bukhara region to determine the productivity of the excavator XE-215CLL for groups 1 and 2 of the group.

It is known that the operational efficiency of an excavator in a shift is calculated using the following expressions and standards. These are q - the capacity of the excavator bucket, m^3 ; Suppose n is the number of operating cycles per minute of the excavator, K_e is the coefficient of utilization of the excavator bucket capacity, K_v is the coefficient of utilization of the excavator in time during the shift. The work done in this case is found as follows [2,3].

Excavator shift performance is calculated using the following expression.

$$\Pi_{\text{счм}} = 492 \cdot q \cdot n \cdot K_e \cdot K_v = 492 \cdot 0,5 \cdot 2,58 \cdot 0,8 \cdot 0,75 = 380,808 \text{ м}^3/\text{счм} \quad (1)$$

where, q is the capacity of the excavator bucket, m^3 ;

n is the number of excavator cycles per minute,

K_e is the excavator bucket capacity utilization factor.

K_v - coefficient of time use per shift

When digging the soil in natural moisture, the hourly operating efficiency of the excavator is found using the following expression.

$$\Pi_{\text{сч}} = \Pi_{\text{счм}} \div 8,2 = 380,808 \div 8,2 = 46,44 \text{ м}^3/\text{сч} \quad (2)$$

If the soils in the channel section are different, then the hourly productivity for each of them is calculated separately and recorded in the specified table.

If the excavated soil is mined, wet or submerged, the hourly work rate is calculated as follows.

$$\Pi_{3,1c} = \Pi_{3c} \div K_{ec} = 46,44 \div 1,25 = 36,4 \text{ m}^3/\text{coat} \quad (3)$$

where the coefficient depending on the depth of water in the Kes-Zaboy is taken from the "Building norms and rules". Cut = 1.25.

During the excavation of the canal, the excavator bucket includes soils with natural moisture and very wet (excavated under water), with different resistance to digging (different groups), so the average measured productivity of the excavator is calculated as follows.

$$\Pi_{3\ddot{y}\ddot{y}} = (\Pi_{3c} \cdot W_2 + \Pi_{3,1c} \cdot W_1) \div (W_1 + W_2) \text{ m}^3/\text{c} \quad (4)$$

Specific working volumes of 1 meter in length, calculated on layers W1, W2, m3 (or for

$$\text{simplification of calculations } W_1 + W_2 = 1 \text{ deb, } W_1 = \frac{W_1}{W_1 + W_2}, W_2 = \frac{W_2}{W_1 + W_2}$$

values are dimensionless, the sum can be used in the form of the values of the additions of one).

Note: Hydraulic excavator bucket capacity 1.0 m3 is less than, the excavator is operated by one machinist, so the machinist's labor consumption rate is equal to the excavator's time consumption norm, if $q > 1.0$ m3. If it is greater than, then the machinist and assistant machinist will work on the excavator, so the machinist's cocktail consumption will be 2 times higher than the excavator's time consumption norm. Using the normative documents, the hourly productivity of the excavator is calculated as follows:

$$\Pi_c^3 = \frac{\ddot{y}\mu\alpha\alpha\mu\mu}{B_m}, \text{ m}^3/\text{coat} \quad (5)$$

where, "gauge" = 100 m3, volume of soil at natural density; V_m - the time consumption rate of the excavator is obtained depending on the type of work, the group of soil and the capacity of the excavator bucket [3].

Under the given conditions, the average hourly productivity of a modern excavator is calculated using existing theories and literature.

Excavator brand - XE-215CLL

There is a Group III soil in the cross section of the canal.

Groundwater level - 0.8 m

Wet soil makes up 30% of the volume of earthworks.

The soil is dug up and dumped on the ground. Using Annex 14 of the Departmental Standards for Repair and Reconstruction and Construction of Land Reclamation Systems and Structures, we record the following in accordance with the above excavator [2].

Digging the ground, leveling the sides and bottom of the canal, draining water from the ditch, digging ditches, and forming rollers to prevent water from flowing. Measuring 100 m3.

XE-215CLL Excavator hourly productivity is calculated using expressions (5), (3) and (4). Here the productivity is calculated using the expression (5) for the second group of soil.

$$\Pi_c^3 = \frac{100}{B_m} = \frac{100}{2,02} = 49,50 \text{ m}^3/\text{c};$$

For wet soils, (3) can be found as follows:

$$P_c^{01} = \frac{P_c^0}{K_{ec}} = \frac{100}{B_m \cdot K_{ec}} = \frac{100}{2,02 \cdot 1,25} = 39,60 \text{ m}^3 / \text{s}$$

The average hourly performance of the excavator is calculated using expression (4).

$$P_{yy}^0 = \frac{P_c^0 \cdot W_2 + P_c^{01} \cdot W_1}{W_1 + W_2} = \frac{49,50 \cdot 0,7 + 39,60 \cdot 0,3}{0,7 + 0,3} = 34,65 + 11,88 = 46,53 \text{ m}^3$$

Calculation of the number and service life of excavators.

When designing a project for the organization of canal construction, it is important to find the number and service life of excavators and as follows

$$N_3 = V \cdot 12 \div D \cdot P_c^0 \cdot K_B \cdot T_{ac}^{01} = 969150 \cdot 12 \div 2000 \cdot 46,53 \cdot 0,75 \cdot 12 = 13,88 \in 14 \text{ дона} \quad (6)$$

In this regard, the following reclamation techniques imported from abroad are used in the region for cleaning and reconstruction of open collector-ditches.

Excavators are currently used in water management organizations and state unitary enterprises in Bukhara region for cleaning and reconstruction of open collector-ditches, taking into account the hydraulic parameters of the collectors. partially restricts access. With this in mind, the selection of an excavator in accordance with the hydraulic parameters of open collector-ditches ensures the quality of subsequent cleaning and repair work and efficient use of excavators. The results of the calculations show that.

No	Adabiyotlar	References
1	З.И.Ж. Худайев, С.Т. Вафоев. Ерларнинг мелиоратив ҳолатини яхшилашда коллектор-дренажларнинг роли. “Суғорма деҳқончиликда ер-сув ресурсларидан оқилона фойдаланишнинг экологик жиҳатлари” мавзусидаги республика илмий – амалий анжумани материаллари тўплами. Бухоро. 2014, 20-23 апрель.Б.- 129-130	З.И.Ж. Xudayev, S.T. Vafoev. The role of collector-drainage in improving the reclamation of lands. Proceedings of the Republican scientific-practical conference "Ecological aspects of rational use of land and water resources in irrigated agriculture." Buxoro. 2014, April 20-23.В.- 129-130.
2	Система машин и технологий для комплексной механизации сельскохозяйственного производства на 2011-2016 гг. Часть III мелиорация. Ташкент, 2015.	The system of machines and technologies for complex mechanization of agricultural production in 2011-2016. Chast III reclamation. Tashkent, 2015.
3	I.S.Hasanov, A.A.Jo'rayev. Suv xo'jaligi va melioratsiya inshootlarini qurish va ta'mirlashda mashinalar tizimini ishlab chiqish bo'yicha izlanishlar. TIMI Buxoro filiali 3-ilmiy – amaliy anjumani ilmiy	.ISHasanov, AAJo'rayev. Research on the development of machine systems in the construction and repair of water management and reclamation facilities. Collection of scientific articles and theses of the 3rd scientific-practical conference of

	maqolalar va tezislar to'plami. Buxoro, 2016.-350 b	the Bukhara branch of TIMI. Buxoro, 2016.-350 p
4	Аҳмаджонов М.А. Ариқ ва зовурларни тозалайдиган машиналардан фойдаланиш. Тошкент, "Ўзбекистон", 1974.- 153 б	Ahmadjonov M.A. Use of machines to clean ditches and ditches. Tashkent, "Uzbekistan", 1974.- 153 p
5	Vafojev S.T. Melioratsiya mashinalari (Darslik). Toshkent, «Fan va texnologiya».2013.-304 b.	Vafojev ST Amelioration machines (Textbook). Tashkent, "Science and Technology". 2013.-304 p.
6	А.Р.Муратов, О.А.Муратов. ИКН В 12.1-2015. Мелиоратив тизимлар ва иншоотларда таъмирлаш-тиклаш ҳамда қурилиш ишларига идоровий нормалар. Расмий нашр. Ўзбекистон Республикаси қишлоқ ва сув хўжалиги вазирлиги. Тошкент, 2015.-156 б.	A.R.Muratov, O.A.Muratov. IKN V 12.1-2015. Departmental norms for repair and reconstruction and construction of reclamation systems and structures. Official publication. Ministry of Agriculture and Water Resources of the Republic of Uzbekistan. Tashkent, 2015.-156 p.
7	“Аму-Бухоро” ирригация тизимлари ҳавза бошқармаси қошидаги Бухоро Мелиоратив экспедициясининг 2016 йил техник ҳисоботи.	Technical report of the Bukhara Ameliorative Expedition under the Amu-Bukhara Irrigation Basin Department for 2016.
8	А.Р.Муратов.“Экскаватор билан канал қазишни ташкил қилиш ва технологияси” мавзули ҳисоб график ишени бажариш бўйича услубий кўрсатма. ТИМИ, 2006.- 44	AR Muratov. Methodical instructions on performance of graphic work on a theme "The organization and technology of excavation of a channel with the excavator". TIMI, 2006.- 44
10	Рахимбоев Ф.М., Ҳамидов М.Ҳ. Қишлоқ хўжалиги мелиорацияси. Тошкент, "Ўзбекистон", 1996. -365 б.	Raximboev F.M., Hamidov M.H. Agricultural reclamation. Tashkent, "Uzbekistan", 1996. -365 p.
11	Муратов А.Р.,Фырлина Г.Л. Комплексная механизация ирригационных и мелиоративных работ:Учебное пособие, -Т.: Изд-во ТИМИ, 2008. -370 с.	Muratov A.R., Fyrlina G.L. Kompleksnaya mekhanizatsiya irrigatsionnyx i meliorativnyx rabot: Uchebnoe posobie, -T. : Izd-vo TIMI, 2008. -370 p.
12	Ахмедов И., Муратов А.Р., Фырлина Г.Л. «Гидромелиоратив ишларни ташкил қилиш ва технологияси» фанидан услубий кўрсатма. ТИКХМИИ, 2002. -16 б.	Axmedov I., Muratov A.R., Fyrlina G.L. Methodical instructions on the subject "Organization and technology of reclamation works". ТИКХМИИ, 2002. -16 p.

13	Ҳасанов И.С., Қўчқоров Ж.Ж., Жўраев А.А. Бухоро вилоятида очиқ коллектор-зовурларни тозалаш ва реконструкция қилишда экскаваторлардан фойдаланишнинг мақбул вариантыни асослаш. Актуальные вызовы современной науки. XIV Международная научная конференция. Сборник научных трудов. Выпуск 6(14), часть 4. Переяслав-Хмельницкий, 26-27 июня 2017г. - 47- 49 с	Hasanov I.S., Kochkarov J.J., Juraev A.A. Substantiation of the optimal option for the use of excavators in the cleaning and reconstruction of open collector-ditches in Bukhara region. Aktualnye vyzovy sovremennoy nauki. XIV International scientific conference. Sbornik nauchnyx trudov. Issue 6 (14), chast 4. Pereyaslav-Khmel'nitskiy, June 26-27, 2017. - 47- 49 p
14	“Delpi”X7 дастурлаш мухитида яратилган «Коллектор-зовурларнинг гидравлик параметрларига мос бир чўмичли гидравлик экскаваторларни мақбуллаштириш» дастури. ТИҚХММИ БФ. Бухоро, 2017	The program "Optimization of single-bucket hydraulic excavators in accordance with the hydraulic parameters of collector-ditches" created in the programming environment "Delpi" X7. TIQXMMI BF. Buxoro, 2017.
15	Meliorativ tizimlar va inshootlarda ta'mirlash-tiklash hamda qurilish ishlari bo'yicha idoraviy me'yorlar. Toshkent 2015. 56 bet.	Departmental standards for repair and construction work on reclamation systems and structures. Tashkent 2015. 56 pages.
16	Toshkent irrigatsiya va melioratsiya institutining “Qishloq va suv xo'jaligining Zamonaviy muammolari” mavzusidagi XIV an'anaviy ilmiy–amaliy anjuman maqolalar to'plami.9-10 aprel II-qism.Toshkent 2015. 56 bet.	Collection of articles of the XIV traditional scientific-practical conference of the Tashkent Institute of Irrigation and Land Reclamation on "Modern problems of agriculture and water management". April 9-10, Part II. Tashkent 2015. 56 pages.
17	Qishloq va suv xo'jaligining zamonaviy muammolari” mavzusida ananaviy ilmiy - amaliy anjuman materialari I I -qism. Toshkent 2013 yil 70- bet.	Proceedings of the traditional scientific-practical conference "Modern problems of agriculture and water management" Part II. Tashkent 2013 page 70
18	JY230ELD, JY230E rusumli zanjirli gidravlik ekskavatorlaridan foydalanish yo'riqnomasi.	Instructions for use of JY230ELD, JY230E chain hydraulic excavators.
19	Ўзбекистон Республикаси Вазирлар Кенгаши ва вилоятлар ҳокимликлари билан биргаликда ишлаб чиқилган қуйидагиларни ўз ичига олган 2013 — 2017 йиллар даврида суғориладиган ерларнинг мелиоратив ҳолатини	The state program on improvement of reclamation of irrigated lands and rational use of water resources for 2013-2017, developed jointly with the Council of Ministers of the Republic of Uzbekistan and regional khokimiyats.

	яхшилаш ва сув ресурсларидан оқилона фойдаланиш давлат дастури.	
20	I.S.Hasanov J.Qo`chqorov U. Hasanov "Yerlarni ekishga tayyorlash texnikalaridan samarali foydalanishga oid" tavsiyalar. Buxoro -2013	IS Hasanov J. Kochkarov U. Hasanov "Recommendations on the effective use of land preparation techniques for planting." Buxoro -2013